

Hebelarmkupplung Vaterteil FF (AG)

EN 14420-7

X Edelstahl



Bestellnummer	Nennweite (DN)	Größe (in Zoll)	Betriebsdruck (in bar)
222800130100	13 (15)	R½" AG	PN16
222800200100	20	R¾" AG	PN16
222800250100	25	R1" AG	PN16
222800320100	32	R1¼" AG	PN16
222800400100	40	R1½" AG	PN16
222800500100	50	R2" AG	PN16
222800650100	65	R2½" AG	PN10
222800800100	80	R3" AG	PN8
222801000100	100	R4" AG	PN7
222801250100	125	R5" AG	PN5
222801500100	150	R6" AG	PN5

EN 14420-7

X Leichtmetall



Bestellnummer	Nennweite (DN)	Größe (in Zoll)	Betriebsdruck (in bar)
222800130200	13 (15)	R½" AG	PN16
222800200200	20	R¾" AG	PN16
222800250200	25	R1" AG	PN16
222800320200	32	R1¼" AG	PN16
222800400200	40	R1½" AG	PN16
222800500200	50	R2" AG	PN16
222800650200	65	R2½" AG	PN10
222800800200	80	R3" AG	PN8
222801000100	100	R4" AG	PN7
222801250100	125	R5" AG	PN5
222801500100	150	R6" AG	PN5

EN 14420-7

X Polypropylen



Bestellnummer	Nennweite (DN)	Größe (in Zoll)	Betriebsdruck (in bar)
222800130300	20	R½" AG	PN5
222800200300	20	R¾" AG	PN5
222800250300	25	R1" AG	PN5
222800320300	32	R1¼" AG	PN5
222800400300	40	R1½" AG	PN5
222800500300	50	R2" AG	PN5
222800800300	80	R3" AG	PN3
222801000300	100	R4" AG	PN3