

Hebelarmkupplung Vatterteil AF (IG, ISO 228, fld.)

X Edelstahl

Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Gewindenorm	Betriebsdruck (in bar)
221300130100	13 (15)	G½" IG	EN 14420-7	PN16
221300200100	20	G¾" IG	EN 14420-7	PN16
221300250100	25	G1" IG	EN 14420-7	PN16
221300320100	32	G1¼" IG	EN 14420-7	PN16
221300400100	40	G1½" IG	EN 14420-7	PN16
221300500100	50	G2" IG	EN 14420-7	PN16
221300650100	65	G2½" IG	EN 14420-7	PN16
221300800100	80	G3" IG	EN 14420-7	PN16
221301000100	100	G4" IG	EN 14420-7	PN10



Hebelarmkupplung Mutterteil DF (IG, ISO 228, fld.)

X Edelstahl

Bestellnummer	Nennweite (DN)	Größe (in Zoll)	Betriebsdruck (in bar)
222310130100	13 (15)	G½" IG	PN16
222310200100	20	G¾" IG	PN16
222310250100	25	G1" IG	PN16
222310320100	32	G1¼" IG	PN16
222310400100	40	G1½" IG	PN16
222310500100	50	G2" IG	PN16
222310650100	65	G2½" IG	PN16
222310800100	80	G3" IG	PN16
222311000100	100	G4" IG	PN10



X Edelstahl

Autolok® - selbstsichernde Handhebel

Bestellnummer	Nennweite (DN)	Größe (in Zoll)	Betriebsdruck (in bar)
229990200100	20	G¾" IG	PN16
229990250100	25	G1" IG	PN16
229990320100	32	G1¼" IG	PN16
229990380100	38	G1½" IG	PN16
229990500100	50	G2" IG	PN16
229990800100	80	G3" IG	PN16