

Sägezahn-Rillenstutzen für Schellenmontage

X Edelstahl



Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Gewindenorm	Betriebsdruck (in bar)
214510130100	13	G½" Ü/M	ISO 228	PN10
214510190100	19	G¾" Ü/M	ISO 228	PN10
214510191100	19	G1" Ü/M	ISO 228	PN10
214510250100	25	G1" Ü/M	ISO 228	PN10
214510320100	32	G1¼" Ü/M	ISO 228	PN10
214510380100	38	G1½" Ü/M	ISO 228	PN10
214510500100	50	G2" Ü/M	ISO 228	PN10
214510650100	65	G2½" Ü/M	ISO 228	PN10
214510651100	65	G3" Ü/M	ISO 228	PN10
214510750100	75	G3" Ü/M	ISO 228	PN10
214511000100	100	G4" Ü/M	ISO 228	PN10

X Messing



Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Gewindenorm	Betriebsdruck (in bar)
214510130400	13	G½" Ü/M	ISO 228	PN10
214510190400	19	G¾" Ü/M	ISO 228	PN10
214510191400	19	G1" Ü/M	ISO 228	PN10
214510250400	25	G1" Ü/M	ISO 228	PN10
214510251400	25	G1¼" Ü/M	ISO 228	PN10
214510320400	32	G1¼" Ü/M	ISO 228	PN10
214510380400	38	G1½" Ü/M	ISO 228	PN10
214510500400	50	G2" Ü/M	ISO 228	PN10
214510650400	65	G2½" Ü/M	ISO 228	PN10
214510750400	75	G3" Ü/M	ISO 228	PN10