

Vaterschlauchverschraubung für Klemmbacken

X Edelstahl

Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in Bar)	Gewindenorm
212000130100	13	R½" AG	PN25	DIN 2999
212000190100	19	R¾" AG	PN25	DIN 2999
212000191100	19	G1" AG	PN25	ISO 228
212000250100	25	G1" AG	PN25	ISO 228
212000251401	25	G1¼" AG	PN25	ISO 228
212000253100	25	G1½" AG	PN25	ISO 228
212000254100	25	G2" AG	PN25	ISO 228
212000320100	32	G1¼" AG	PN25	ISO 228
212000322100	32	G1½" AG	PN25	ISO 228
212000321100	32	G2" AG	PN25	ISO 228
212000380100	38	G1½" AG	PN25	ISO 228
212000381100	38	G2" AG	PN25	ISO 228
212000500100	50	G2" AG	PN25	ISO 228
212000501100	50	G2½" AG	PN25	ISO 228
212000630100	63	G2½" AG	PN25	ISO 228
212000631100	63	G3" AG	PN25	ISO 228
212000650100	63/65	G2½" AG	PN25	ISO 228
212000651100	63/65	G3" AG	PN25	ISO 228
212000750100	75	G3" AG	PN25	ISO 228
212000800100	80	G3" AG	PN25	ISO 228
212001000100	100	G4" AG	PN25	ISO 228

Fragen Sie Ihren DIFLEX-Fachberater auch nach **Stutzen mit NPT Gewinde**.



X Edelstahl / ECTFE

Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in Bar)	Gewindenorm
212000250101	25	G1" AG	PN25	ISO 228
212000320101	32	G1¼" AG	PN25	ISO 228
212000380101	38	G1½" AG	PN25	ISO 228
212000381101	38	G2" AG	PN25	ISO 228
212000500102	50	G2" AG	PN25	ISO 228
212000750102	75	G3" AG	PN25	ISO 228
212001000101	100	G4" AG	PN25	ISO 228

