

Vaterschlauchverschraubung für Klemmbacken

X Leichtmetall



Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in Bar)	Gewindenorm
212000750200	75	G3" AG	PN16	ISO228
212001000200	100	G4" AG	PN16	ISO228

X Messing



Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in Bar)	Gewindenorm
212000130400	13	R½" AG	PN25	DIN 2999
212000190400	19	R¾" AG	PN25	DIN 2999
212000191400	19	G1" AG	PN25	ISO 228
212000250400	25	G1" AG	PN25	ISO 228
212000251400	25	G1¼" AG	PN25	ISO 228
212000253400	25	G1½" AG	PN25	ISO 228
212000252400	25	G2" AG	PN25	ISO 228
212000320400	32	G1¼" AG	PN25	ISO 228
212000322400	32	G1½" AG	PN25	ISO 228
212000321400	32	G2" AG	PN25	ISO 228
212000380400	38	G1½" AG	PN25	ISO 228
212000381400	38	G2" AG	PN25	ISO 228
212000400400	40	G1½" AG	PN25	ISO 228
212000401400	40	G2" AG	PN25	ISO 228
212000450400	45	G2" AG	PN25	ISO 228
212000500400	50	G2" AG	PN25	ISO 228
212000501400	50	G2½" AG	PN25	ISO 228
212000630400	63	G2½" AG	PN25	ISO 228
212000631400	63	G3" AG	PN25	ISO 228
212000651400	63/65	G3" AG	PN25	ISO 228
212000750400	75	G3" AG	PN25	ISO 228
212000800400	80	G3" AG	PN25	ISO 228
212001000400	100	G4" AG	PN25	ISO 228

X Polypropylen



Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in bar)	Gewindenorm
212000250300	25	G1" AG	PN6	ISO 228
212000320300	32	G1¼" AG	PN6	ISO 228
212000380300	38	G1½" AG	PN6	ISO 228
212000500300	50	G2" AG	PN6	ISO 228
212000750300	75	G3" AG	PN6	ISO 228