

Mutterschlauchverschraubung für Klemmbacken

X Edelstahl

Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in bar)	Gewindenorm
212500130100	13	G½" Ü/M	PN25	ISO 228
212500131100	13	G¾" Ü/M	PN25	ISO 228
212500190100	19	G¾" Ü/M	PN25	ISO 228
212500191100	19	G1" Ü/M	PN25	ISO 228
212500250100	25	G1" Ü/M	PN25	ISO 228
212500251100	25	G1¼" Ü/M	PN25	ISO 228
212500252100	25	G1½" Ü/M	PN25	ISO 228
212500320100	32	G1¼" Ü/M	PN25	ISO 228
212500321100	32	G1½" Ü/M	PN25	ISO 228
212500322100	32	G2" Ü/M	PN25	ISO 228
212500380100	38	G1½" Ü/M	PN25	ISO 228
212500381100	38	G2" Ü/M	PN25	ISO 228
212500500100	50	G2" Ü/M	PN25	ISO 228
212500501100	50	G2½" Ü/M	PN25	ISO 228
212500630100	63	G2½" Ü/M	PN25	ISO 228
212500650100	63 / 65	G2½" Ü/M	PN25	ISO 228
212500750100	75	G3" Ü/M	PN25	ISO 228
212501000100	100	G4" Ü/M	PN25	ISO 228



X Edelstahl

Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in bar)	Gewindenorm
212500253100	25	S60 x 6 Ü/M	PN25	DIN 6063-1-KS60
212500383100	38	S60 x 6 Ü/M	PN25	DIN 6063-1-KS60
212500502100	50	S60 x 6 Ü/M	PN25	DIN 6063-1-KS60



X Edelstahl

Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in bar)	Gewindenorm
212500751100	75	Ww 5½" Ü/M	PN25	DIN 11
212501001100	100	Ww 5½" Ü/M	PN25	DIN 11



X Edelstahl / ECTFE

Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in bar)	Gewindenorm
212500250101	25	G1" Ü/M	PN25	ISO 228
212500320101	32	G1¼" Ü/M	PN25	ISO 228
212500380101	38	G1½" Ü/M	PN25	ISO 228
	38	G2" Ü/M	PN25	ISO 228
212500500101	50	G2" Ü/M	PN25	ISO 228
212500750101	75	G3" Ü/M	PN25	ISO 228
212501000101	100	G4" Ü/M	PN25	ISO 228

