

Mutterschlauchverschraubung für Klemmbacken

X Messing



Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in bar)	Gewindenorm
212500130400	13	G½" Ü/M	PN25	ISO 228
212500131400	13	G¾" Ü/M	PN25	ISO 228
212500190400	19	G¾" Ü/M	PN25	ISO 228
212500191400	19	G1" Ü/M	PN25	ISO 228
212500250400	25	G1" Ü/M	PN25	ISO 228
212500251400	25	G1¼" Ü/M	PN25	ISO 228
212500252400	25	G1½" Ü/M	PN25	ISO 228
212500320400	32	G1¼" Ü/M	PN25	ISO 228
212500321400	32	G1½" Ü/M	PN25	ISO 228
212500322400	32	G2" Ü/M	PN25	ISO 228
212500350400	35	G1½" Ü/M	PN25	ISO 228
212500351400	35	G2" Ü/M	PN25	ISO 228
212500380400	38	G1½" Ü/M	PN25	ISO 228
212500381400	38	G2" Ü/M	PN25	ISO 228
212500400400	40	G1½" Ü/M	PN25	ISO 228
212500401400	40	G2" Ü/M	PN25	ISO 228
212500450400	45	G2" Ü/M	PN25	ISO 228
212500500400	50	G2" Ü/M	PN25	ISO 228
212500501400	50	G2½" Ü/M	PN25	ISO 228
212500630400	63	G2½" Ü/M	PN25	ISO 228
212500650400	63 / 65	G2½" Ü/M	PN25	ISO 228
212500651400	63 / 65	G3" Ü/M	PN25	ISO 228
212500750400	75	G3" Ü/M	PN25	ISO 228
212500800400	80	G3" Ü/M	PN25	ISO 228
212501000400	100	G4" Ü/M	PN25	ISO 228

X Messing



Bestellnummer	Nennweite (DN)	Gewinde (in Zoll)	Betriebsdruck (in bar)	Gewindenorm
212500751400	75	Ww 5½" Ü/M	PN16	DIN 11
212501001400	100	Ww 5½" Ü/M	PN16	DIN 11