

Anschweißschlauchstutzen für Klemmbacken

X Edelstahl

Bestellnummer	Nennweite (DN)	Betriebsdruck (in bar)	Anschweißende (in mm)
214000130100	13	PN16	21,3 x 2,0
214000190100	19	PN16	26,9 x 2,3
214000250100	25	PN16	33,7 x 2,6
214000320100	32	PN16	42,4 x 2,6
214000380100	38	PN16	48,3 x 2,6
214000500100	50	PN16	60,3 x 2,9
214000630100	63	PN16	76,1 x 2,9
214000650100	65	PN16	76,1 x 2,9
214000750100	75	PN16	88,9 x 3,2
214001000100	100	PN16	114,3 x 3,6



X Stahl

Bestellnummer	Nennweite (DN)	Betriebsdruck (in bar)	Anschweißende (in mm)
214000130500	13	PN16	21,3 x 2,0
214000190500	19	PN16	26,9 x 2,3
214000250500	25	PN16	33,7 x 2,6
214000320500	32	PN16	42,4 x 2,6
214000380500	38	PN16	48,3 x 2,6
214000500500	50	PN16	60,3 x 2,9
214000630500	63	PN16	76,1 x 2,9
214000650500	65	PN16	76,1 x 2,9
214000750500	75	PN16	88,9 x 3,2
214001000500	100	PN16	114,3 x 3,6



Schlauchverbinder für Klemmbacken

X Edelstahl

EN 14420-2

Bestellnummer	Nennweite (DN)	Betriebsdruck (in bar)
210000130100	13	PN16
210000190100	19	PN16
210000250100	25	PN16
210000320100	32	PN16
210000380100	38	PN16
210000500100	50	PN16
210000650100	63/65	PN16
210000750100	75	PN16
210001000100	100	PN16

