

Klemmbacken inkl. Schrauben und Muttern

- Norm: EN14420-3
- Betriebsdruck: PN25

X Edelstahl

Bestellnummer	Nennweite (DN)	Schlauch Außen-ø (in mm)	Anzahl Schrauben & Muttern
152000130100	13 x 5	22-24	4 x M6 x 20
152000190101	19 x 4	26-29	4 x M6 x 20
152000190100	19 x 6	30-33	4 x M6 x 20
152000250101	25 x 5	34-36	4 x M6 x 20
152000250100	25 x 6	36-39	4 x M6 x 20
152000320100	32 x 6	43-46	4 x M6 x 20
152010320100	32 x 8	47-50	4 x M6 x 20
152000380100	38 x 6,5	50-52	4 x M6 x 20
152000381100	38 x 8	53-56	4 x M6 x 20
152000401100	40 x 10	58-61	4 x M6 x 20
152020500100	50 x 6	61-63	4 x M8 x 25
152000500100	50 x 8	64-67	4 x M8 x 25
152010500100	50 x 10	69-71	4 x M8 x 25
152000630101	63 x 6	74-76	4 x M8 x 25
152000630100	65 x 7	78-82	4 x M8 x 25
152000750101	75 x 6,5	87-89	4 x M8 x 25
152000750100	75 x 8	89-93	4 x M8 x 25
152001000100	100 x 8	114-119	4 x M10 x 40



X Messing

Bestellnummer	Nennweite (DN)	Schlauch Außen-ø (in mm)	Anzahl Schrauben & Muttern
152000130400	13 x 5	22-24	4 x M6 x 20
152000190400	19 x 6	30-33	4 x M6 x 20
152000250400	25 x 6	36-39	4 x M6 x 20
152000320400	32 x 6	43-46	4 x M6 x 20
152010320400	32 x 8	47-50	4 x M6 x 20
152000380400	38 x 6,5	50-52	4 x M6 x 20
152000500400	50 x 8	64-67	4 x M8 x 25
152010500400	50 x 10	69-71	4 x M8 x 25
152000630400	65 x 7	78-82	4 x M8 x 25
152000750400	75 x 8	89-93	4 x M8 x 25
152001000400	100 x 8	114-119	4 x M10 x 40

