

Klemmbacken für Dampf

- für Schalenstutzen
- inkl. Schrauben und Muttern
- max. Betriebsdruck: Dampf & Heißwasser max. 18 bar
- Temperaturbereich: Dampf & Heißwasser max. 210°C

EN 14423

X Messing

Bestellnummer	Nennweite (DN)	Schlauch Außen-ø (in mm)	Anzahl Schrauben & Muttern
400013050400	13 x 5 (½")	22-24	4 x M6 x 20
400013060400	13 x 6 (½")	24-26	4 x M6 x 20
400013070400	13 x 7 (½")	26-28	4 x M6 x 20
400019060400	19 x 6 (¾")	30-33	4 x M8 x 25
400019070400	19 x 7 (¾")	32-34	4 x M8 x 25
400025065400	25 x 6,5 (1")	37-39	4 x M8 x 25
400025075400	25 x 7,5 (1")	39-41	4 x M8 x 25
400025085400	25 x 8,5 (1")	41-43	4 x M8 x 25
400032060400	32 x 6 (1¼")	43-46	4 x M8 x 25
400032080400	32 x 8 (1¼")	47-50	4 x M8 x 25
400038080400	38 x 8 (1½")	53-56	4 x M10 x 40
400050090400	50 x 9 (2")	67-69	4 x M10 x 40
400050100400	50 x 10 (2")	69-71	4 x M10 x 40
400065120400	65 x 12 (2½")	88-91	4 x M10 x 40



EN 14423

X Edelstahl

Bestellnummer	Nennweite (DN)	Schlauch Außen-ø (in mm)	Anzahl Schrauben & Muttern
400013060100	13 x 6 (½")	22-24	4 x M6 x 20
400019070100	19 x 7 (¾")	32-34	4 x M8 x 25
400025075100	25 x 7,5 (1")	39-41	4 x M8 x 25
400032080100	32 x 8 (1¼")	47-50	4 x M8 x 25
400038080100	38 x 8 (1½")	53-56	4 x M10 x 40
400050090100	50 x 9 (2")	67-69	4 x M10 x 40

