

Tri-Clampdichtung, Reihe A

Bestellnummer	Nennweite (DN)	Clamp AD (in mm)	Clamp ID (in mm)	Werkstoff
501334131604	15	34	16.2	FKM grün
501334192004	19	34	20.2	FKM grün
501350192604	25	50.5	26.2	FKM grün
501350323204	32	50.5	32.2	FKM grün
501350383804	38	50.5	38.2	FKM grün
501364505004	50	64	50.2	FKM grün
501391636604	63	91	66.2	FKM grün
501334131617	15	34	16.2	NBR weiss
501334192017	19	34	20.2	NBR weiss
501350192617	25	50.5	26.2	NBR weiss
501350323217	32	50.5	32.2	NBR weiss
501350383817	38	50.5	38.2	NBR weiss
501364505017	50	64	50.2	NBR weiss
501391636617	63	91	66.2	NBR weiss
501334131612	15	34	16.2	PTFE
501334192012	19	34	20.2	PTFE
501350192612	25	50.5	26.2	PTFE
501350323212	32	50.5	32.2	PTFE
501350383812	38	50.5	38.2	PTFE
501364505012	50	64	50.2	PTFE
501391636312	63	91	66.2	PTFE
501334131602	15	34	16.2	EPDM schwarz
501334192002	19	34	20.2	EPDM schwarz
501350252602	25	50.5	26.2	EPDM schwarz
501350323202	32	50.5	32.2	EPDM schwarz
501350383802	38	50.5	38.2	EPDM schwarz
501364505002	50	64	50.2	EPDM schwarz
501391656602	63	91	66.2	EPDM schwarz

NBR
FKM
PTFE

Weitere Informationen

- DIN 32676
- Reihe B und C auf Anfrage
- weitere Nennweiten auf Anfrage



Perrot Kardangelenk-Dichtung

Bestellnummer	Nennweite (DN)	Werkstoff
501500500036	2" - 50	SBR schwarz
501500650036	2½" - 70	SBR schwarz
501500800036	3" - 89	SBR schwarz
501501000036	4" - 108	SBR schwarz
501501250036	5" - 133	SBR schwarz
501501500036	6" - 159	SBR schwarz
501502000036	8" - 216	SBR schwarz

SBR schwarz

