

NBR gelb



Weitere Informationen

- auch in 3 mm Höhe lieferbar.
- für Wellrohre.

Oval-Flanschdichtungen NBR gelb

Bestellnummer	Nennweite (DN)	Innen-Ø (in mm)	Länge (in mm)	Breite (in mm)	Lochabstand (in mm)	Ø-Loch (in mm)	Höhe (in mm)
502100200022	20	23	76	46	58	10	2
502100250022	25	27	90	55	68	12	2
502100320022	32	36	100	64	78	11	2
502100400022	40	43	104	68	82	12	2
502100500022	50	52	126	80	100	12	2

Klingsil C4500



Weitere Informationen

- auch in 3 mm Höhe lieferbar.
- für Wellrohre.

Oval-Flanschdichtungen Klingsil C4500

Bestellnummer	Nennweite (DN)	Innen-Ø (in mm)	Länge (in mm)	Breite (in mm)	Lochabstand (in mm)	Ø-Loch (in mm)	Höhe (in mm)
502100200023	20	23	76	46	58	10	2
502100250023	25	27	90	55	68	12	2
502100320023	32	36	100	64	78	11	2
502100400023	40	43	104	68	82	12	2
502100500023	50	52	126	80	100	12	2

Novapress 850 / Novaform 2300



Weitere Informationen

- auch in 3 mm Höhe lieferbar.
- für Wellrohre.

Oval-Flanschdichtungen Novapress 850 / Novaform 2300

Bestellnummer	Nennweite (DN)	Innen-Ø (in mm)	Länge (in mm)	Breite (in mm)	Lochabstand (in mm)	Ø-Loch (in mm)	Höhe (in mm)
501162000030	20	23	76	46	58	10	2
501162500030	25	27	90	55	68	12	2
501163200030	32	36	100	64	78	11	2
501164000030	40	43	104	68	82	12	2
501165000030	50	52	126	80	100	12	2