


Klingersil

C4400/PTFE ummantelt




Weitere Informationen

- Blattdicke 0,5 mm
- Einlage 2,0 mm

Flanschdichtungen Klingersil C4400 / PTFE ummantelt

Bestellnummer	Nennweite (DN)	Norm	Außen-Ø (in mm)	Innen-Ø (in mm)	Höhe (in mm)	
502000250010	25	PN 10/40	71	34	3	
502000320010	32	PN 10/40	82	43	3	
502000400010	40	PN 10/40	92	49	3	
502000500010	50	PN 10/40	107	61	3	
502000650010	65	PN 10/40	127	77	3	
502000800010	80	PN 10/40	142	89	3	
502001000010	100	PN 10/16	162	115	3	
502001250010	125	PN 10/16	192	141	3	
502001500010	150	PN 10/16	218	169	3	
502002000010	200	PN 10/16	273	220	3	
Bestellnummer	Nennweite (DN)	Norm	Lochkreis (in mm)	Lochzahl	Ø-Loch (in mm)	Maß (in mm)
502000800110	80	TW 1	130	8	12	154 x 90 x 3
502001000110	100	TW 3	150	8	14	174 x 110 x 3
502001250110	125	TW 5	176	8	14	204 x 135 x 3
502001500110	150	TW 7	210	12	14	240 x 160 x 3
502001500210	150	Spitzer	210	8	14	230 x 150 x 3
502002000110	200	Feldbinder	248	6	13	270 x 200 x 3

Novapress 850 / Novaform 2300



Weitere Informationen

- Zulassungen: Blow-out VDI 2200, DVGW, EG 1935/2004, FDA, GL, TA Luft, Trinkwasser gemäß Elastomerleitlinie („KTW“), VP 401, W 270, WRAS

Quadrat-Flanschdichtungen Novapress 850 / Novaform 2300

Bestellnummer	Nennweite (DN)	Außenmaß (in mm)	Innen-Ø (in mm)
502409044030	Gaspindelventil	90x90x2	44
502409070030		90x90x2	70
502409860030	Flugfeld-Tankwagen	98x98x2	60
502409860030		98x98x2	60
502410055030	Bodenventil, flach	100x100x2	55
502410065030	Treibschieberzähler	100x100x2	65
502410580030		105x105x2	80
502411590030		115x115x2	90
502411780030		117x117x2	80
502412580030		125x125x2	80
502413090030		130x130x2	90
502413010030	TQFA 100 Lm	130x130x2	100
502415510030		155x155x2	100
502416095030	TW 610	160x160x2	95
502416012030		160x160x2	120